

23.08.00

10/049752

REC'D 12 SEP 2000

WIPO PCT



מדינת ישראל  
STATE OF ISRAEL

Ministry of Justice  
Patent Office

משרד המשפטים  
לשכת הפטנטים

1800/00985

4

This is to certify that annexed  
hereto is a true copy of the  
documents as originally  
deposited with the patent  
application of which  
particulars are specified on the  
first page of the annex.

זאת לתעודה כי רצופים  
בזה העתקים נכונים של  
המסמכים שהופקדו  
לכתחילה עם הבקשה  
לפטנט לפי הפרטים  
הרשומים בעמוד הראשון  
של הנספח.

**PRIORITY  
DOCUMENT**

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

20-07-2000

This \_\_\_\_\_ היום

מ. ל. סל  
רשם הפטנטים  
Commissioner of Patents

נתאשר  
Certified

לשימוש הלשכה  
For Office Use

131837	מספר: Number
09-09-1999	תאריך: Date
הוקדם/נדחה Ante/Post-dates	

חוק הפטנטים, התשכ"ז -- 5727-1967  
PATENTS LAW, 5727-1967

בקשה לפטנט

Application for Patent

C:35108

אני, (שם המבקש, מענו -- ולגבי גוף מאוגד -- מקום התאגדותו)  
I (Name and address of applicant, and, in case of body corporate-place of incorporation)

ORBOTECH-SCHUH GMBH & CO LTD.

P.O. Box 215

Yavne 81102

אורבotech-שו ג.מ.ב.ה. בע"מ

ת.ד. 215

יבנה 81102

(An Israeli company)

(חברה ישראלית)

By Law ששמה הוא

Owner, by virtue of

בעל אמצאה מכח הדין

of an invention, the title of which is:

מערכת בדיקה אופטית מאוטמטת בעלת שדה ראייה משופר (בעברית)  
(Hebrew)

AUTOMATED OPTICAL INSPECTION SYSTEM WITH IMPROVED FIELD OF VIEW (באנגלית)  
(English)

hereby apply for a patent to be granted to me in respect thereof

מבקש בזאת כי ינתן לי עליה פטנט

*בקשה חלוקה - Application for Division		*בקשת פטנט מוסף - Application for Patent of Addition		*דרישה דין קדימה Priority Claim		
מבקשת פטנט from Application		*לבקשה/לפטנט to Patent/Appl.		מספר/סימן Number/Mark	תאריך Date	מדינת האיגוד Convention Country
No. _____ מס. dated _____ מיום		No. _____ מס. dated _____ מיום				
*יפוי כת: כללי/מיוחד - רצוף בזה / עוד יוגש P.O.A.: general / individual - attached / to be filed later - הוגש בעניין _____						
המען למסירת הודעות ומסמכים בישראל Address for Service in Israel Sanford T. Colb & Co. P.O.B. 2273 Rehovot 76122						
חתימת המבקש Signature of Applicant For the Applicant,  Sanford T. Colb & Co. C:35108				היום 8 בחודש September שנת 1999 This of of the year		
				לשימוש הלשכה For Office Use		

טופס זה, כשהוא מוטבע בחותם לשכת הפטנטים ומושלם בספר ובתאריך ההגשה, הינו אישור להגשת הבקשה שפרטיה רשומים לעיל.  
This form, impressed with the Seal of the Patent Office and indicating the number and date of filing, certifies the filing of the application, the particulars of which are set out above.

\* מחק את המיותר Delete whatever is inapplicable

מערכת בדיקה אופטית מאוטמטת בעלת שדה ראייה משופר

AUTOMATED OPTICAL INSPECTION SYSTEM WITH IMPROVED FIELD OF  
VIEW

ORBOTECH-SCHUH GMBH & CO. LTD.  
C: 35108

אורבוטק-שו ג.מ.ב.ה. בע"מ

## AUTOMATED OPTICAL INSPECTION SYSTEM WITH IMPROVED FIELD OF VIEW FIELD OF THE INVENTION

The present invention relates generally to automated optical inspection systems and particularly to an automated optical inspection system with an improved and efficient field of view.

### BACKGROUND OF THE INVENTION

Automated optical inspection (AOI) systems are typically used to inspect such items as printed circuit boards onto which components are mounted ("loaded PCB's") and the like. As seen in Fig. 1, prior art AOI systems for inspecting loaded PCB's typically employ four (4) CCD cameras 1, 2, 3 and 4, arranged north, east, south and west at an angle above an area to be inspected. Optionally, a fifth CCD camera may be provided positioned atop the area to be inspected. The field of view for commonly used CCD cameras is substantially rectangular, typically having a width/height (i.e., horizontal/vertical) ratio of 4/3.

In current AOI systems, the CCD sensors view a horizontal region and each camera has the same field of view. It is seen in Fig. 1 that the fields of view of cameras 1 and 3 extend to dashed lines 5 and the fields of view of cameras 2 and 4 extend to dashed lines 6. However, the actual working field of view 7 is only the area in the middle where the fields of view from both sets of opposing cameras overlap. Thus some portions of the fields of view of the cameras are not utilized, making the system somewhat inefficient.

### SUMMARY OF THE INVENTION

The present invention seeks to provide an automated optical inspection system with an improved and efficient field of view.

There is thus provided in accordance with a preferred embodiment of the present invention an automated optical inspection system including four CCD cameras spaced from each other and arranged generally north, east, south and west at an angle above a generally rectangular area upon which an item to be inspected may be placed, wherein a width of the area is larger than a height of the area, each of the cameras having an optical axis and a field of view, the fields of view of the cameras being generally rectangular, wherein a width of the field of view is larger than a height of the field of view, characterized in that a pair of the cameras are positioned generally opposite each other, each having the width and height of their fields of view generally in the same direction as the width and height of the area, respectively, and the other pair of the cameras are positioned generally opposite each other

and generally perpendicular to the first-mentioned pair of cameras, each having the width and height of their fields of view generally in the same direction as the height and width of the area, respectively.

5 In accordance with a preferred embodiment of the present invention the fields of view of both pairs of the cameras overlap generally at a common area.

Further in accordance with a preferred embodiment of the present invention the fields of view of the cameras each have a width/height ratio of about 4/3.

10 Still further in accordance with a preferred embodiment of the present invention a fifth camera is positioned generally atop the generally rectangular area. Preferably the field of view of the fifth camera overlaps the fields of view of the other cameras generally at a common area.

Additionally in accordance with a preferred embodiment of the present invention the fifth camera comprises an array of cameras, and the combined field of view of the array generally corresponds to the generally rectangular area.

#### 15 BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be understood and appreciated more fully from the following detailed description, taken in conjunction with the drawings in which:

Fig. 1 is a simplified pictorial illustration of a prior art automated optical inspection system; and

20 Fig. 2 is a simplified pictorial illustration of an automated optical inspection system constructed and operative in accordance with a preferred embodiment of the present invention.

#### DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

25 Reference is now made to Fig. 2 which illustrates an automated optical inspection system 10 constructed and operative in accordance with a preferred embodiment of the present invention.

30 Automated optical inspection system 10 preferably includes four CCD cameras 12, 14, 16 and 18, spaced from each other and arranged generally north, east, south and west at an angle above an area 15 upon which an item to be inspected may be placed. (It is appreciated, of course, that the terms "north, east, south and west" are relative and are not necessarily connected to the directions of a true compass.) Optionally, a fifth CCD camera 19 may be placed atop the area to be inspected. The fifth camera 19 may comprise an array of cameras 19A, 19B, 19C and 19D, for example. The area 15 is generally rectangular, i.e., a

width W of area 15 is larger than a height H of area 15, such as a width/height ratio of about 4/3.

Each camera has an optical axis 20 and a field of view 22. The fields of view are generally rectangular, i.e., a width of the field of view is larger than a height of the field of view, such as a width/height ratio of about 4/3. It is appreciated that because of the angled arrangement of the cameras, the field of view may be slightly trapezoidal.

It is a particular feature of the present invention that the fields of view of two of the cameras positioned generally opposite each other, for example, cameras 14 and 18, are each rotated generally 90° about their optical axis. In other words, cameras 12 and 16 each have the width and height of their fields of view generally in the same direction as the width and height of area 15, respectively, and cameras 14 and 18 each have the width and height of their fields of view generally in the same direction as the *height* and *width* of area 15, respectively.

In such an arrangement, the fields of view of the cameras overlap generally at a common area, preferably a substantially rectangular working field of view. The field of view of optional top camera 19 (or cameras 19A, 19B, 19C and 19D) also preferably generally overlaps this common working field of view. This increases the working field of view and ultimately improves system speed, even though the same cameras of the prior art are employed. This also obviates the need for relatively expensive square field-of-view cameras.

As is well known in the art, rectangular field-of-view cameras may have associated with them a keystone problem, wherein the rectangular field of view becomes distorted trapezoidally. The keystone problem can be reduced or eliminated with appropriate adjustment of optics configuration and/or with algorithms, for example, relying on the so-called "Scheimpflug Principle", or other methods used in the art.

It will be appreciated by persons skilled in the art that the present invention is not limited by what has been particularly shown and described hereinabove. Rather the scope of the present invention includes both combinations and subcombinations of the features described hereinabove as well as modifications and variations thereof which would occur to a person of skill in the art upon reading the foregoing description and which are not in the prior art.

## CLAIMS

What is claimed is:

1. An automated optical inspection system comprising:

four CCD cameras spaced from each other and arranged generally north, east, south and west at an angle above a generally rectangular area upon which an item to be inspected may be placed, wherein a width of the area is larger than a height of the area, each of said cameras having an optical axis and a field of view, the fields of view of said cameras being generally rectangular, wherein a width of the field of view is larger than a height of the field of view;

characterized in that a pair of said cameras are positioned generally opposite each other, each having the width and height of their fields of view generally in the same direction as the width and height of the area, respectively, and the other pair of said cameras are positioned generally opposite each other and generally perpendicular to the first-mentioned pair of cameras, each having the width and height of their fields of view generally in the same direction as the height and width of the area, respectively.

2. The system according to claim 1 wherein the fields of view of both pairs of said cameras overlap generally at a common area.

3. The system according to claim 1 or claim 2 wherein the fields of view of said cameras each have a width/height ratio of about 4/3.

4. The system according to any of claims 1-3 and further comprising a fifth camera positioned generally atop said generally rectangular area.


5. The system according to claim 4 wherein the field of view of said fifth camera overlaps the fields of view of the other cameras generally at a common area.

6. The system according to claim 4 wherein said fifth camera comprises an array of cameras, and wherein the combined field of view of the array generally corresponds to said generally rectangular area.

7. The system according to any of claims 1-4 and substantially as described hereinabove.

For the Applicant,

Sanford T. Colb & Co.  
Advocates & Patent Attorneys  
C:35108








FIG. 2

**THIS PAGE BLANK (USPTO)**